

Podium Waterproofing

Method of Application:-

a) Surface preparation

The surface to be coated must be solid and clean, free of all traces of coatings, efflorescence, loose particles, grease, oil, demoulding agents, dust, gypsum plaster, etc. Remove by water pressure cleaning

b) Treatment of Junction Any corner or concrete slab-wall joint/junction should be opened with a chisel to a size of 3 x 3 cm, avoiding "V" shape and fill the groove with Polymer Modified

Mortar. These grooves should be finished in a shape of a cove to provide a smooth edge.

- Waterproofing with Isothane / Techothane (Polyurethane single component)
- Waterproofing with Flexible Cementitious Coating
- Waterproofing with Acrylic Polymer Based Cementitious Coating

Why Click Zippy?

- **ASSURITY**
if any Mistake done by our professional then we can give again best services is free of cost after surety of wrong services.
- **Service totally done by trained professionals within time limit that means fast services.**
- **Professional service is affordable rate so you can satisfied your need.**
- **We are based on application and website so Customer can book online services at their place and get services at doorstep.**
- **Easy comparison of Qualitative services and their rate.**
- **Broad category of services we have.**

GIRIBALA CREATIVE VENTURES PVT.LTD.

CIN: U74999GJ2017PTC097068

1007, North Plaza, Near Dmart Visat Gandhinagar Highway, Motera, Ahmedabad, Gujarat, India-380005

Website: www.clickzippy.com

Download App: Click Zippy

Email: info@clickzippy.com

Mo/What's app: 99249 64118, (079)40025494

National Award for E-Governance-2019